



## **!! URGENT !!**

**Date:** 12 October 2018

**Subject:** Ali Al Salem, Kuwait  
Ali Al Salem AB (OKAS)  
ILS or LOC Rwy 30L  
Cycle 1811

### ***Incorrect Localizer Frequency***

Jeppesen NavData for cycle 1811, effective 11 October 2018, contains incorrect localizer frequency for IASB localizer for runway 30L. The correct frequency for IASB localizer is 108.9 with DME channel 26X.

Revised coding will appear in Jeppesen NavData for cycle 1812, effective 8 November 2018. Until then an entry will appear in the NavData Change Notices, and this Alert will be posted on the Jeppesen Web site (<http://www.jeppesen.com/company/alerts/alerts.jsp>). Please refer to the Ali Al Salem AB (OKAS) 31-2 chart dated 20 APR 18 (effective 26 Apr) for valid information.

**WE STRONGLY URGE YOU TO MAKE THIS INFORMATION AVAILABLE TO  
APPROPRIATE CREW MEMBERS OR CUSTOMERS IMMEDIATELY!**

If you have questions concerning this NavData Alert, please contact Jeppesen Technical Support at:

Phone: 1-303-328-4445

E-mail: [navdatatechsupport@jeppesen.com](mailto:navdatatechsupport@jeppesen.com)

NavData Alerts are published to advise users of significant issues in Jeppesen navigation data which may affect flight operations or safety. They are distributed to affected ARINC 424 NavData users (avionics companies and other raw data users) and airlines receiving NavData directly from Jeppesen. Alerts are not distributed by Jeppesen to individual airline, business aviation or general aviation pilots, but are available to them on the Jeppesen Web site, [www.jeppesen.com](http://www.jeppesen.com). Different avionics equipment and computer systems use and display NavData and data derived from NavData differently. Avionics users should consult with their database update service provider for definitive information on whether their system is affected by this Alert.

OKAS 1811